


HOW TO INSTALL


STEP 1

Have your device ready on a soft, lint-free towel. Make sure the device is OFF. Unpack your CLOAK box so that your squeegee, spray bottle and CLOAK are ready.



STEP 2

Spray your fingers with the solution. It is KEY to easy application. Your fingers should ALWAYS be wet when handling the CLOAK.




STEP 3

Carefully remove the CLOAK screen protector.



STEP 4

With the application solution, spray the sticky side of CLOAK so that it is completely wet. Carefully lay the CLOAK on your device, going edge to edge when laying it down, and slide it into place. We recommend using any cut-outs and edges as a guide for placement.




STEP 5

Keeping CLOAK steady with 1 hand, lightly squeegee from the center outwards to remove excess solution and air. Do not squeegee towards openings such as the microphone or speaker. If fluid does get into these areas, blot the fluid out with a Q-Tip or towel. Using your towel, lightly pat around the edges to remove any solution that was squeegeed out.




STEP 6

Wet the tip of your squeegee using the solution, then squeegee CLOAK again, applying slightly more pressure this time. Gently wipe away excess fluid.




STEP 7

Allow to set for 5 minutes.



STEP 8

Let your device sit for 1 hour with the power OFF. It is normal during this time to see corners or edges lift up. Simply push them back down and hold them for 15 seconds with moderate pressure using your thumb or palm. After an hour you can use your device normally.



LIFETIME WARRANTY

We'll replace your CLOAK any time for any reason.

FOR ALL WARRANTY CLAIMS:

Please contact TYLT customer service. Phone: (800) 843-5600 Email: customerservice@TYLT.com

iPhone is a trademark of Apple Inc., registered in the U.S. and other countries.